

AirGuard

Wheel Sensor, TPMS

Herth+Buss wheel sensors can be used in all vehicles that have a tyre pressure monitoring system installed as standard. The AirGuard is required for programming and adjustment to the vehicle concerned. This process only takes between 5 and 15 seconds per sensor. An outstanding feature of the Herth+Buss wheel sensors: the original serial/ID number can be copied from the "old" sensor to the new one, or can be reassigned. In addition, the wheel sensors can be rewritten, used in aluminium

and steel rims and wirelessly activated. The sensors can be ordered individually and are supplied with the complete valve in standard silver. A valve repair kit is also available, as are replacement valves in silver and black.

- one for all: optimum stockage with just one universal wheel sensor
- valves with adjustable angles
- for steel or aluminium rims
- certification up to 250 km/h
- battery service life: 3-7 years

to Tightening torque: 4 Nm
Material: Aluminium
Pressure: to 9 bar
Weight: 46 g
only in connection with: 95990001

Info: with battery
 with pressure sensor
 with integrated air temperature sensor
 with seal
 with box nut
 with screw
 with valves

Frequency Range MHz	Information Transfer	DU	Article no.
433	Radio	1	70699443
Content		QU	
Valve, TPMS AirGuard		1	70699433013
Accessories		see	DU
Programming-/Diagnostic Unit, TPMS AirGuard		Katalog08	1 95990001
Valve Repair Set (TPMS) AirGuard		Katalog08	4 70699433012
Valve, TPMS AirGuard		Katalog08	1 70699433014

